


TL32K

series



Product Segments

• Ergo Motion


TiMOTION's TL32K series is a lower-cost, high-value lifting column specifically designed for ergonomic desks, work tables, and other height-adjustable systems. Work surfaces adapt quietly and smoothly with synchronous movement. The TL32K is compatible with TC series Control Boxes and TH/ TDH series controls, and it can be controlled quietly and smoothly with synchronous movement. All Ergo Motion TC series control boxes have a less than 0.1W standby power option that reduces power consumption. Our wide range of columns offers solutions to satisfy customers' working environment project requirements. The TL32K has a two-stage telescopic profile designed for a narrow-top, wide-bottom rectangular appearance.

General Features

Max. load	600N (push)
Max. speed at max. load	31mm/s
Max. speed at no load	38mm/s
Retracted length	Standard (compatible with foot): 645mm Extended (compatible with shoe): 665mm
Dimension of outer tube	83*53mm rectangular
Stages	2 stage
Stroke	500mm
Output signals	Hall sensors
Voltage	24V DC
Color	Black, white, grey, or special grey
With motor house	

Drawing

Standard Dimensions
(mm)



Load and Speed

CODE	Load (N)	Self Locking Force (N)	Typical Current (A)		Typical Speed (mm/s)	
	Push		No Load 29V DC	With Load 29V DC	No Load 29V DC	With Load 29V DC
D	600	600	2.2	6	38	31

Motor Speed (5200RPM)


Note

- Above self lock, typical current and typical speed performance are tested with Timotion control boxes.
- Parameters above are from tested average, please refer to approval drawing for final value.


Performance Data (24V DC Motor)

Motor Speed (5200RPM)

Speed vs. Load



Current vs. Load



Note

1 The performance data in the curve charts shows theoretical value.

Appearance of Motor House	C = TiMOTION standard			
Voltage	2 = 24V DC			
Load and Speed	See page 2			
Stroke & Retracted Length (mm)	See page 5			
Color	1 = Black, RAL 9005	2 = White, RAL 9016	3 = Grey, RAL 9006	4 = Special grey, RAL 9022
Wiper Color	1 = Black	2 = White	3 = Grey	4 = Matte black
Bracket	0 = Without			
Bottom Plate Type	1 = M10	2 = M6		
Bottom Plate Height	1 = Standard		2 = Extended outer tube for shoe	
Output Signals	2 = Hall sensor * 2			
Connector	1 = DIN 6P, 90° plug		F = Molex 8P, 90° plug, without anti-clip, for TC22/TC23	
See page 5	E = Molex 8P, 180° plug, standard			
Cable Length (mm)	1 = Straight, 500	3 = Straight, 1000	4 = Straight, 1500	

Note

¹ The TL is designed especially for push applications, not suitable for pull applications.


Stroke & Retracted Length (mm)

Foot Assembly	Stroke & Retracted Length
	Standard
Standard, for Foot (Excluding Foot)	500 / 645
Extended Outer Tube for Shoe (Excluding Shoe)	500 / 665

Note


1 Only specific TEK could be with the shoes, please refer to TEK speccode.

Foot Assembly




Connector


1 = DIN 6P, 90° plug



E = Molex 8P, 180° plug, standard



F = Molex 8P, 90° plug, without anti-clip, for TC22/TC23



Terms of Use

The user is responsible for determining the suitability of TiMOTION products for a specific application. TiMOTION products are subject to change without prior notice.